


Ausfahren (extend): 267N / 482N  
Einfahren (retract): 220N / 415N

	Grundkoerper basic build L1 [mm]	Schlitten slide L2 [mm]	gesamte Masse total mass [kg]		bewegte Masse moved mass [kg]	F [N]	F [N]	M [Nm]	
			KEE 0025	KEE 0032					
Nennhub (rated lift)	0300	450	460	7.80	8.19	3.70	60	210	25
	0250	400	410	7.22	7.57	3.47	70	255	25
	0200	350	360	6.65	6.98	3.25	80	300	25
	0160	310	320	6.19	6.48	3.07	100	320	25
	0125	275	285	5.80	6.06	2.92	110	380	25
	0100	250	260	5.51	5.37	2.81	125	400	25
	0080	230	240	5.27	5.50	2.72	150	440	25
	0050	200	210	4.93	5.14	2.58	175	500	25
	0040	190	200	4.80	5.00	2.54	200	520	25
	0025	175	185	4.65	4.84	2.47	260	560	25
	0010	160	170	4.47	4.65	2.41	280	580	25



zul. Belastung fuer 6000km Hub  
max. permissible for 6000km lift

Bestellangaben:  
order code:

Kurzhubeinheit KEE 00\_\_\_\_  
short stroke unit

normal / spiegelbildlich  
regular / in reverse image

Nennhub: 0010, 0025, 0040, 0050, 0080,  
rated lift: 0100, 0125, 0160, 0200, 0250,  
0300

Zylinderdurchmesser: 25, 32  
cylinder diameter: